


TESATAST Standard Models



	mm				
01810005	0,01	0,8	28	0 ÷ 0,4 ÷ 0	12,53
01810006	0,01	0,8	38	0 ÷ 0,4 ÷ 0	12,53
01810007	0,01	0,5	28	0 ÷ 0,25 ÷ 0	36,53
01810008	0,01	0,5	38	0 ÷ 0,25 ÷ 0	36,53
01810009	0,002	0,2	28	0 ÷ 100 ÷ 0	12,53
01810010	0,002	0,2	38	0 ÷ 100 ÷ 0	12,53
S18001695	0,001	0,2	38	0 ÷ 100 ÷ 0	12,53



	in				
01820006	0.0005	0.030	1.1	0 ÷ 15 ÷ 0	1/2
01820007	0.0005	0.030	1.5	0 ÷ 15 ÷ 0	1/2
01820008	0.0005	0.020	1.1	0 ÷ 10 ÷ 0	1 7/16
01820009	0.0005	0.020	1.5	0 ÷ 10 ÷ 0	1 7/16
01820010	0.001	0.030	1.1	0 ÷ 15 ÷ 0	1/2
01820011	0.0001	0.008	1.1	0 ÷ 4 ÷ 0	1/2
01820012	0.0001	0.008	1.5	0 ÷ 4 ÷ 0	1/2
01820013	0.00005	0.008	1.5	0 ÷ 4 ÷ 0	1/2

SWISSTAST Standard Models




	mm				
01811000	0,01	0,8	28	0 ÷ 0,4 ÷ 0	12,53
01811001	0,002	0,2	38	0 ÷ 100 ÷ 0	12,53

* Same technical data as standard models, but equipped with a 2 mm dia. ruby ball tip No. 01860302.

TESATAST Perpendicular Models



	mm				
01810204	0,01	0,8	28	0 ÷ 0,4 ÷ 0	12,53
01810205	0,01	0,5	28	0 ÷ 0,25 ÷ 0	36,53
01810304	0,002	0,2	38	0 ÷ 100 ÷ 0	12,53



	in				
01820204	0.0005	0.030	1.1	0 ÷ 15 ÷ 0	1/2
01820304	0.0001	0.008	1.5	0 ÷ 4 ÷ 0	1/2



DIN 2270
NF E 11-053

Rotating dial

Very low
measuring force
see table
on page G-3

Movement with
patented shock
proof system

Lever system
with friction
drive to prevent
overload

Accuracy:
see table on
page G-3

Supplied in
a plastic case
along with:

1 Insert with a 2 mm dia.
1 Wrench (No. 01860307)
1 Mounting rod with a 8 mm
dia. (No. 01840105)

Identification
number

Declaration
of conformity